Subject Index for
Electronics and Communications in Japan, Part 2, Volume 77, 1994

Absorption line of Rb atoms: **3**, 1-11
Absorption loss measurement: **5**, 12-20
Access network: **12**, 67-77
Active carbon fiber: **6**, 98-107
Active filter: **1**, 99-107
Active-matrix liquid crystal display: **7**, 38-45
Adhesion mechanism: **5**, 57-69
Aging effect: **6**, 54-61
AlInAs/GaInAs HEMT: **8**, 35-44
Aluminum-gate TFTs: **7**, 38-45
Amorphous silicon thin-film transistor: **7**, 38-45
Amplification of electromagnetic waves: **6**, 1-9
AM/PM conversion: **3**, 50-57
Analog telephone components: **3**, 40-49
Analysis method: **6**, 72-80
Anisotropic optical waveguide: **9**, 21-28
Anisotropy: **2**, 20-28
Anodic oxidation: **12**, 59-66
Anodized silicon: **4**, 97-105; **9**, 56-64
Aperture integration method: **8**, 91-101
Arbitrary coordinate system: **1**, 26-34
Arc discharge: **9**, 48-55
Array: **7**, 28-37; **10**, 57-66
Astable multivibrator: **8**, 64-72
Auger electron spectroscopy: **12**, 59-66

Backplane power supply: **6**, 90-97
Bandpass filter: **1**, 46-56; **3**, 66-73
Beam-charge density modulation component: **11**, 89-97
Beam scanning: **9**, 95-104
Beam-propagation method: **5**, 32-38
Bentonite: **9**, 105-114; **12**, 96-106
Berlekamp-Massey algorithm: **11**, 56-68
Bi-CMOS: **2**, 65-76
Bi_2Te_3: **12**, 38-47
Bidirectional optical transmission: **9**, 74-84
Binary digital phase hologram: **11**, 1-14
Bipolar: **2**, 65-76
Biquadratic filter: **1**, 99-107
Bit-wide: **2**, 65-76
Block-erasing method: **4**, 106-113
Body of revolution: **2**, 1-11
Boron: **5**, 47-56
Boundary condition: **1**, 15-25
Boundary element method: **2**, 39-45
Burial scale: **9**, 105-114
Buried heterostructure laser: **2**, 29-38
Butt-joined coupling: **2**, 20-28

Cascade module: **12**, 38-47
Cellular portable telephone: **3**, 58-65
Cellular radio: **4**, 38-50
Ceramic waveguide: **4**, 51-57
Čerenkov laser: **3**, 12-19; **6**, 1-9
Channel optical waveguide: **9**, 21-28
Channel-to-channel interference: **12**, 78-88
Charging of the signal voltage: **7**, 38-45
Chiral medium: **4**, 69-74
Chirality admittance: **4**, 69-74
Circuit card backplane: **6**, 90-97
Circuit theory: **1**, 15-25; **7**, 65-76; **10**, 82-93
Circular polarization: **9**, 95-104
Cl_2 plasma etching: **8**, 24-34
Clamp electrical field: **6**, 54-61
CMOS: **2**, 65-76
CMOS quartz crystal oscillator: **6**, 72-80
Color display: **6**, 81-89
Color plasma display: **10**, 94-103
Comparators: **8**, 1-13
Complex eigenenergy level: **5**, 106-115
Composite lubricants: **9**, 74-84
Computer-aided design: **11**, 15-24
Computer simulation: **11**, 1-4
Contact: **2**, 88-95; **9**, 48-55
Contact resistance: **6**, 62-71
Contact spot: **2**, 88-95
Contact sticking: **1**, 87-98
Contact supporting arm: **1**, 87-98
COP: **12**, 38-47
Coplanar waveguide: **3**, 66-73
Core network: **12**, 67-77
Coulomb blockage: **9**, 65-73
Coupled mode equation: **6**, 21-29
Coupling: **7**, 28-37
Coupling coefficient: **6**, 21-29
Coupling efficiency: **8**, 45-53
Crossover: **1**, 26-34
Crosstalk: **4**, 88-96; **6**, 81-89
Crosstalk analysis: **1**, 26-34

Crystal oscillator: **9**, 39-47
Cu metallization technology: **1**, 108-116
Cu-Nb materials: **9**, 74-84
Cu-Su materials: **9**, 74-84
Current constriction: **2**, 88-95
Current conveyor: **1**, 99-107
Current density distribution: **2**, 88-95
Current distribution method: **8**, 91-101
Current injected control: **12**, 89-99
Current-mode: **1**, 99-107
Current runaway: **12**, 89-99
$CuTi_2$ intermetallic compound: **1**, 108-116
Cutoff frequency: **7**, 77-91
Cylindrical model: **4**, 97-105

3-D image display: **2**, 77-87
Data-disturb suppression: **4**, 106-113
3 dB coupling: **4**, 51-57
DC-DC connector: **12**, 89-99
DC drift: **11**, 37-51
Delay: **4**, 58-68
Delay line: **3**, 20-27
Demodulator: **4**, 29-37
Device noise: **7**, 11-20
DFT: **2**, 46-55
Dielectric constant: **3**, 74-82
Dielectric resonator: **3**, 58-65
Dielectric waveguide: **2**, 12-19; **12**, 20-27
Diffraction: **8**, 14-23
Diffusion: **5**, 47-56
Diffusion barrier: **1**, 108-116
Digital cellular: **3**, 50-57
Digital magnetic recording: **8**, 73-81
Digital mobile communication: **3**, 66-73
Digital modulation: **4**, 10-19
Direct conversion receiver: **4**, 29-37
Direct-contact imaging: **8**, 54-63
Directional coupler: **4**, 51-57; **11**, 62-72
Discharge: **10**, 94-103
Discontinuous variation: **1**, 35-45
Displacement sensor: **10**, 13-21
Dissipation factor: **12**, 59-66
Drain current drift: **1**, 66-76
Driver integration technology: **7**, 46-55
Dual frequency: **9**, 95-104
Duplexer: **4**, 38-50
Dynamic behavior: **3**, 12-19
Dynamic characteristics: **8**, 82-90

Eigenenergy level: **5**, 106-115
Eigenmode expansion method: **5**, 39-46
Electric power output: **5**, 93-105
Electrical conduction mechanism: **1**, 77-86
Electrical contacts: **1**, 87-98; **9**, 74-84
Electroluminescence: **6**, 54-61
Electron microscope: **6**, 98-107
Electron waveguide: **9**, 12-20
Electronic circuit: **1**, 99-107; **7**, 65-76
Electrooptic constants: **5**, 1-11; **12**, 28-37
Electrooptic crystal: **5**, 21-31
Electrooptic effect: **10**, 22-32
Elliptic mode-field: **7**, 28-37
Energy conservation relation: **3**, 12-19
Energy level: **6**, 54-61
Environmental degradation: **12**, 100-110
Equalizer: **4**, 58-68
Equivalent aperture plane: **8**, 91-101
Equivalent capacitance: **6**, 72-80
Equivalent circuit: **4**, 1-9
Er-doped silica-based optical waveguide: **11**, 62-72
Error diffusion method: **11**, 1-14
Etalon: **10**, 57-66
Excimer laser: **2**, 56-64
Extrapolation: **6**, 30-38

Facsimile: **5**, 70-85
Faraday medium: **1**, 35-45
Fast frequency switching: **4**, 20-28
FD-TD method: **12**, 20-27
Ferroelectric liquid crystal: **1**, 1-14
FET amplifier: **3**, 28-39
Filter switching: **4**, 20-28
Filtering: **2**, 46-55
Finesse: **11**, 15-24
Finite element method: **2**, 39-45, 88-95; **4**, 69-74; **5**, 32-38, 39-46; **6**, 1-9; **9**, 21-28; **11**, 15-24; **12**, 1-9
Finite-difference time-domain method: **1**, 26-34
Fixed-charge density: **6**, 54-61
Flash memory: **4**, 106-113
Fluoride fiber: **4**, 75-87
Fractal: **6**, 98-107
Fractional N phase-locked loop: **4**, 20-28
Frequency dispersion: **11**, 82-88
Frequency divider: **8**, 64-72
Frequency stabilization: **3**, 1-11; **10**, 57-66
Frequency synthesizer: **4**, 20-28; **7**, 1-10
FSK: **4**, 29-37
FTTH: **9**, 74-84

GaAs: **9**, 1-11; **11**, 82-88
GaAs FET: **3**, 40-49; **4**, 1-9
GaAs pin photodiode: **1**, 1-14

GaAs power module: **3**, 40-49
GaAs/AlxGa1-xAs: **1**, 15-25
GaInAs pin PD: **8**, 35-44
GaInAsP/InP: **2**, 29-38
Galerkin method: **5**, 39-46
Gap: **2**, 20-28
Gate-busline delay: **7**, 38-45
Gaussian trap distribution: **1**, 77-86
Graded-index optical waveguide: **9**, 21-28
Grating coupler: **10**, 13-21
Ground resistance: **9**, 105-114; **12**, 100-110
Guided modes in an open waveguide: **2**, 39-45

Half-wavelength voltage: **12**, 28-35
Hardness: **4**, 97-105
Heat transfer analysis: **5**, 70-85
Heat transfer coefficient: **5**, 12-20
Hermite-Gaussian functions: **10**, 1-12
High-capacity network: **12**, 67-77
High-density optical disc player: **7**, 92-104
High efficiency: **3**, 28-39
High-frequency dc/dc converter: **2**, 105-113
High output: **3**, 28-39
High permittivity: **4**, 51-57
High-permittivity ceramics: **1**, 46-56
High relative refractive difference (high-Δ) waveguide: **11**, 25-36a
High-resistance epitaxial: **7**, 77-91
High-Tc superconductor: **2**, 56-64
Higher-order modes: **6**, 10-20, 30-38
HUFFLE gate: **10**, 104-114
Hybrid optical circuit: **10**, 57-66
Hybrid optical integration: **10**, 67-81
Hybrids: **8**, 1-13

IcRn product: **1**, 57-65
Image process: **6**, 98-107
Image sensor: **8**, 54-63
Improvement of reconstructed image: **11**, 1-14
InAs/(AlGa)Sb heterostructure: **1**, 57-65
InAs/GaSb: **1**, 15-25
Inclination: **2**, 20-28
Infrared optical fiber: **5**, 12-20
InGaAs: **1**, 66-76
Inhomogeneous chirowaveguide: **4**, 69-74
Integral equation: **9**, 12-20
Integrated circuit: **6**, 81-89; **7**, 65-76
Integrated coupling device: **8**, 45-53
Integrated optics: **10**, 13-21
Integrated pin photodiode sensor: **7**, 77-91
Integration: **11**, 73-81
Integration of optical devices: **12**, 1-7
Interaction: **5**, 57-69
Interface: **5**, 57-69
Intermetallic compound: **5**, 57-69
Intermodulation product: **11**, 89-88
Isolation: **9**, 95-104

Jitter correction: **7**, 92-104
Josephson effect: **3**, 74-82
Josephson logic gate: **10**, 104-114
Junction FET (JFET): **7**, 11-20

Kerr-like medium: **6**, 1-9

Large deployable antenna: **8**, 91-101
Large-sized matrix display: **7**, 105-120
Laser array: **7**, 21-27
Laser diode: **8**, 45-53
Laser oscillation: **11**, 62-72
Lateral misalignment: **2**, 20-28
Least square approximation: **10**, 1-12
Least-squares problem: **2**, 1-11
LED: **6**, 39-43
Level characteristics: **6**, 72-80
Lift-off process: **1**, 57-65
Lightning surge: **8**, 102-114
$LiNbO_3$: **10**, 57-66
$LiNbO_3$ optical modulator: **9**, 74-84
Line source: **8**, 14-23
Line width: **11**, 62-72
Linear modulation: **3**, 50-57
Linear polarization: **9**, 95-104
Liquid crystal microdroplet: **12**, 48-58
Liquid phase epitaxial growth: **10**, 22-32
$LiTaO_3$ waveguide: **5**, 1-11
Lithium niobate: **10**, 22-32; **11**, 37-51; 52-61
Load-pull method: **3**, 28-39
Low distortion amplifier: **6**, 81-89
LSI interconnects: **3**, 93-105

Magnetic field modulation: **6**, 44-53, 108-118
Magneto-optic disk: **6**, 44-53
Magneto-optical effect: **3**, 1-11
Magnetoelastic wave: **3**, 20-27
Magnetooptical disk: **6**, 108-118
Magnetooptical recording: **3**, 83-92
Magnetostatic wave: **3**, 20-27
Master slice: **7**, 77-91
Mechanochemical reaction: **6**, 62-71
Memory array block division: **4**, 106-113
MESFET: **11**, 82-88

Metal multilayers: **5**, 57-69
Metal-semiconductor contacts: **1**, 108-116
Metallic phase arc: **9**, 48-55
Metallic phase arc duration: **9**, 48-55
Microlens: **8**, 45-53
Microstrip: **3**, 74-82
Microwaves: **4**, 58-68; **6**, 30-38
8, 1-13
Miller integral: **8**, 64-72
Millimeter-wave integrated circuit: **2**, 12-19
Millimeter waves: **4**, 58-68
Miniaturization: **1**, 46-56
Miniband: **5**, 106-115
MISFET: **1**, 66-76; **2**, 56-64
Mobile communication: **9**, 1-11
Mobile radio system: **7**, 1-10
Mode coupling theory: **12**, 8-16
Mode-field converting (MFC) fiber: **7**, 28-37
Mode-matching method: **9**, 29-38
Modified Viterbi deconding: **3**, 83-92
Moisture: **6**, 62-71
Moment method: **9**, 12-20
Monolithic integration: **7**, 11-20; **11**, 99-112
Monte Carlo simulation: **9**, 65-73
MOS analog circuit: **7**, 65-76
MQW structures: **10**, 33-44
Multilayered dielectric thin films: **12**, 59-66
Multilayered MMIC: **1**, 26-34
Multimode laser: **12**, 10-19
Multiple branch circuits: **8**, 1-13
Multipulse recording: **6**, 108-118

Natural single-phase unidirectional transducer: **12**, 1-9
Nb-based superconducting film: **2**, 96-104
Negative resistance: **6**, 72-80
Networks: **12**, 67-77
n/m code: **3**, 83-92
Nonlinear analysis: **5**, 93-105
Nonlinearity: **4**, 38-50
Nonorthogonal FD-TD method: **12**, 20-27
Nonparallel: **6**, 21-29
Nonsymmetrical triple barrier: **10**, 82-93
Numerical analysis: **9**, 21-28
Numerical calculation: **8**, 82-90

Offset loss: **10**, 1-12
Open failure: **3**, 93-105
Open-boundary structure: **3**, 12-19
Operational circuit: **4**, 88-96
Operational transconductance amplifier (OTA): **7**, 65-76
Optical amplifier: **11**, 73-81
Optical bistability: **1**, 35-45
Optical CATV: **9**, 74-84
Optical coherence: **12**, 10-19
Optical communication: **12**, 67-77
Optical connection: **10**, 45-56
Optical detector: **4**, 88-96
Optical directional coupler: **12**, 20-27
Optical disk drive: **4**, 88-96
Optical FDM: **12**, 78-88
Optical fiber: **7**, 28-37
Optical fiber amplifier: **4**, 75-87
Optical fiber communication: **2**, 29-38
Optical integrated circuits: **11**, 15-24
Optical interference measurement method: **12**, 10-19
Optical interferometer: **10**, 13-21
Optical measurement: **12**, 10-19
Optical modulator: **11**, 37-51
Optical parallel process: **10**, 45-56
Optical parallel processing: **1**, 1-14
Optical rotary angle: **12**, 28-37
Optical rotary power: **5**, 21-31
Optical sensing: **1**, 35-45
Optical sensitivity: **5**, 21-31
Optical shutter: **2**, 77-87
Optical simulation: **8**, 54-63
Optical SSB signal: **12**, 78-88
Optical switch: **11**, 73-81; **12**, 1-7
Optical voltage sensor: **5**, 21-31; **12**, 28-37
Optical VSB signal: **12**, 78-88
Optical waveguide: **10**, 1-12; **11**, 15-24, 37-51, 52-61
Oscillator: **3**, 58-65
Overcurrent limited mode: **12**, 89-99
Oxalate method in ethanol solution: **2**, 77-87
Oxygen concentration: **1**, 77-86

Palladium oxide: **6**, 62-71
Partial response system: **3**, 83-92
Partial response systems: **8**, 73-81
Passive circuit elements: **8**, 1-13
Peltier device: **12**, 38-47
Periodic potential: **5**, 106-115
Perpendicular magnetic recording: **8**, 73-81
Personal computer: **6**, 30-38
Phase: **4**, 58-68
Phase characteristics: **4**, 1-9
Phase modulation method: **5**, 1-11
Phase noise: **3**, 58-65; **4**, 20-28
Phase-locked loop (PLL): **7**, 1-10
Photodiode: **7**, 11-20
Photonic devices: **7**, 28-37; **8**, 24-34

Photonic integrated circuit: **11**, 99-112
Photonic integrated devices: **10**, 33-44; **11**, 99-112
Photonic switching: **11**, 73-81
Photopolymerization-induced phase separation: **12**, 48-58
Pit-edge recording: **6**, 108-118
Pixel arrangement: **7**, 105-120
Planar grating: **2**, 46-55
Planar lightwave circuit on silicon: **10**, 67-81
Planar lightwave circuits: **11**, 25-36
Planar power components: **2**, 105-113
PLZT electrooptical effect: **2**, 77-87
Polar molecule: **9**, 56-64
Polarization direction control: **1**, 35-45
Poly-silicon thin film transistor (TFT): **7**, 46-55
Polyhedron-approximated antenna: **8**, 91-101
Polymer-dispersed liquid crystal: **12**, 48-58
Polyvinylalcohol: **12**, 48-58
Porosity: **9**, 56-64
Porous structure: **4**, 97-105
Power-added efficiency: **4**, 10-19
Power amplifier: **3**, 50-57; **4**, 1-9
Power conversion efficiency: **5**, 93-105
Power magnetics: **2**, 105-113
Pr^{3+}-doped fiber: **4**, 75-87
Pressure: **6**, 62-71
Private network: **12**, 67-77
PRML system: **8**, 73-81
Process-simulator: **3**, 106-115
Proton exchange: **5**, 1-11
Pulse memory drive: **10**, 94-103
Pulse number: **8**, 64-72

QPSK: **3**, 50-57; **9**, 1-11
Quadrature mixer: **4**, 29-37
Quadrature modulator: **9**, 1-11
Quantum well: **5**, 106-115
Quantum-level control: **10**, 33-44
Quasi-CMOS inverter: **9**, 65-73
Quasiphase match: **11**, 52-61
Quasi-three-dimensional: **3**, 106-115

Radio: **4**, 38-50
Raman spectroscopy: **5**, 86-92
Reactive ion beam etching: **8**, 24-34
Readout waveform simulation: **6**, 44-53
Receiver: **2**, 12-19
Receiver OEIC: **8**, 35-44
Reciprocity theorem: **6**, 21-29
Recording method: **5**, 70-85
Reducing material: **9**, 105-114; **12**, 100-110
Reflected light: **9**, 74-84
Reflectometry: **12**, 10-19
Relativistic electron beam: **3**, 12-19
Reliability: **3**, 93-105
Resonant converter: **8**, 82-90
Resonator: **3**, 66-73, 74-82
Response time: **9**, 56-64
Ring resonator: **11**, 62-72

Saturated absorption spectroscopy: **3**, 1-11
SAW resonator: **4**, 38-50
Scattering: **8**, 14-23
Scattering loss measurement: **5**, 12-20
Scattering problem: **2**, 46-55
Scattering property: **9**, 29-38
Second-harmonic generation: **11**, 52-61
Seebeck coefficient: **5**, 93-105
Selective growth: **7**, 21-27
Selective metal organic chemical vapor deposition (MOCVD) growth: **10**, 33-44
Self-aligned drain contact: **4**, 10-19
Self-diplexing antenna: **9**, 95-104
Self-standing limit: **4**, 97-105
III/IV semiconductor: **8**, 24-34
Semiconductor: **9**, 12-20; **11**, 99-112
Semiconductor laser: **2**, 29-38; **3**, 1-11; **7**, 21-27
Shadowing effect: **3**, 106-115
SHG device: **11**, 37-51
Si power MOSFET: **4**, 10-19
^{29}Si solid-state NMR: **5**, 86-92
SiGe: **5**, 47-56
Silanol: **9**, 56-64
Silica-based waveguide: **11**, 25-36
Silver contact material: **9**, 48-55
Simulation: **2**, 88-95
Single-electron tunneling: **9**, 65-73
Single resonant level: **10**, 82-93
Singularity: **6**, 10-20
SiN_x: **6**, 39-43
SIPOS film: **1**, 77-86
Sliding friction: **9**, 74-84
Smith chart: **10**, 82-93
Sn-Sb solder: **5**, 57-69
Sol-gel method: **5**, 86-92
Solid lubricants: **9**, 74-84
Spatial light modulator: **1**, 1-14
Spectral domain method: **8**, 14-23
Spot size: **10**, 1-12
Spurious response: **3**, 66-73
SRAM: **2**, 65-76
State transition matrix: **8**, 82-90
Stress: **3**, 93-105; **5**, 47-56

Strip conductor: **8**, 14-23
Subjective evaluation test of picture quality: **7**, 105-120
Submicrometer metal gate: **4**, 10-19
Superconducting integrator circuit: **10**, 104-114
Superconducting transistor: **1**, 57-65
Superconducting weak links: **1**, 57-65
Surface acoustic wave (SAW) filter: **4**, 38-50
Surface acoustic wave interdigital electrode: **12**, 1-9
Surface-emitting laser vertical cavity: **2**, 29-38
Surface mount: **4**, 51-57
Surface-mounted device: **1**, 46-56
Surface operating optoelectronic devices: **10**, 45-56
Surface resistance: **3**, 74-82
Surface state density: **1**, 66-76
Surface trap: **11**, 82-88
Surge impedance: **8**, 102-114
Switched capacitor: **8**, 64-72
Symmetrical structure: **9**, 29-38

Taper: **4**, 58-68; **6**, 30-38
TCN (temperature-compensated network): **9**, 39-47
TCXO (temperature-compensated crystal oscillator): **9**, 39-47
Telecommunications equipment subrack assembly: **6**, 90-97
Telephone center building: **8**, 102-114
Temperature coefficient: **6**, 39-43; **12**, 28-37
TFD fabrication and testing: **7**, 56-64
TFD liquid crystal display (LCD): **7**, 56-64
TFT on glass substrate: **7**, 46-55
Theory: **1**, 35-45
Thermal expansion: **5**, 12-20
Thermal head: **5**, 70-85
Thermal recording: **5**, 70-85
Thermally diffused expanded core (TEC) fibers: **12**, 1-7
Thermoelectric element: **5**, 93-105
Thermoelectric power generation: **5**, 93-105
Thick-film printing: **10**, 94-103
Thin film: **10**, 22-32
Thin-film capacitors: **12**, 59-66
Thin-film diode (TFD): **7**, 56-64
Thomson coefficient: **5**, 93-105
Three-axis optical head: **7**, 92-104
Three-dimensional: **3**, 106-115
Three-dimensional Nyquist limits: **7**, 105-120
Three-dimensional problem: **2**, 1-11
Three-inch diameter InP substrate: **8**, 35-44
Threshold value: **1**, 35-45
Ti silicide: **1**, 108-116
Topography simulator: **3**, 106-115
Tracking offset: **6**, 44-53
Transfer problem: **5**, 39-46
Transmittance: **6**, 39-43
Transmitter: **2**, 12-19
Transparent boundary: **5**, 32-38
Trap density: **1**, 77-86
Traveling wave optical modulators: **10**, 22-32
Traveling-wave tube: **11**, 89-98
TTL: **2**, 65-76
Two-beam laser diode: **4**, 88-96
Two-dimensional array: **10**, 45-56
Two-dimensional chirowaveguide: **4**, 69-74
Two-port quartz crystal resonator: **9**, 39-47
TZ amplifier: **7**, 77-91

UHF: **3**, 28-39
Undercoating film: **12**, 48-58
Unidirectional electrode: **12**, 1-9

VCO: **3**, 58-65
VCTCXO (voltage-controlled temperature compensated crystal oscillator): **9**, 39-47
Viterbi decoding: **8**, 73-81

Wall TV set: **10**, 94-103
Water-absorbent material: **9**, 105-114
Water-absorbing material: **12**, 100-110
Wavefunction: **1**, 15-25
Waveguide: **4**, 58-68; **6**, 10-20, 30-38
Waveguide filter: **1**, 46-56
Waveguide junction: **9**, 29-38
Waveguide technology: **10**, 67-81
Wideband phase-shifer: **4**, 29-37
Wideband video amplifier: **6**, 81-89
Write power margin: **6**, 44-53

Γ-X mixing: **1**, 15-25

Yasuura method: **2**, 1-11; **6**, 10-20
YIG thin film: **3**, 20-27
Yule-Nielsen effect: **8**, 54-63

Zeebeck coefficient: **12**, 38-47
Zero-sequence voltage: **5**, 21-31